

Approved  YES  NO

Approved By: \_\_\_\_\_

Date: \_\_\_\_\_

# MAXSEAL

## STANDARD SYSTEM INCLUDES

- DIRECT DRIVE MOTOR, UP TO 48ips OPENING SPEED
- NEMA 4, WALL MOUNTED, VARIABLE FREQUENCY PROGRAMMABLE CONTROLLER
- 40oz VINYL CURTAIN: COLOR \_\_\_\_\_
- ALUMINUM GUIDES
- ALUMINUM BREAKAWAY BAR
- ELECTRICAL SAFETY EDGE
- LINTEL BRUSH SEAL
- REFLECTIVE PHOTO EYE

## MECHANICAL / ELECTRICAL OPTIONS

- EXTERIOR HOOD & MOTOR COVER
- GUIDE BRUSH SEALS
- KEY LOCK FOR FALCON SENSOR
- THRU BEAM PHOTO EYE
- NEMA 4 3-BUTTON STATION
- FALCON EYE AND BRACKET
- LOOP DETECTOR
- WIRELESS RECEIVER
- WIRELESS TRANSMITTER: QTY. \_\_\_\_\_
- FLANGE MOUNT DISCONNECT
- LIGHT CURTAIN SYSTEM

### ELECTRICAL CRITERIA:

CONTROL PANEL NEMA/EEMAC 4 STD. OR \_\_\_\_\_  
 PRIMARY POWER SUPPLY: 460 V, 3 Phase

### NOTES:

CLIENT: \_\_\_\_\_

DEALER: \_\_\_\_\_

Drive: *Right Hand Drive*



(484) 840 - 8500  
 5 Crozerville Road | Aston, PA 19014

DRAWN	DATE	NAME
	12/12/2016	CLATSIOS
CHECKED	12/12/2016	

MaxSeal  
 \_ ft (W) x \_ ft \_ in (H)

COPYRIGHT: The design and engineering content shown on this drawing remains the property of PERFORMAX, and may not be copied in any way without prior written approval from the company.

Drawing Number  
 MAXSEAL

Rev.  
 0

